

Product Name: LIQUIDOW* Technical Grade Calcium Chloride
Solution

Issue Date: 01/02/2007 Print Date: 05 Jan 2007

* Indicates a Trademark Page 1 of 8

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions

actions.

1. Product and Company Identification

Product Name

LIQUIDOW* Technical Grade Calcium Chloride Solution

COMPANY IDENTIFICATION

The Dow Chemical Company

2030 Willard H. Dow Center

Midland, MI 48674

USA

Customer Information Number:

800-258-2436

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 989-636-4400

Local Emergency Contact: 989-636-4400

2. Hazards Identification

Emergency Overview

Color: Clear

Physical State: Liquid

Odor: Odorless

Hazards of product:

WARNING! Causes eye irritation. Prolonged exposure may cause skin burns.

Slipping hazard. Isolate area.

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29

CFR 1910.1200.

Potential Health Effects

Eye Contact: May cause severe eye irritation. May cause slight corneal injury. Effects may be slow to heal.

Skin Contact: skin is abraded (scratched or cut). May cause more severe response on covered skin (under clothing,

Material Safety Data Sheet

The Dow Chemical Company

Product Name: LIQUIDOW* Technical Grade Calcium Chloride
Solution

Issue Date: 01/02/2007 Page 2 of 8

gloves). Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Inhalation: Mist may cause irritation of upper respiratory tract (nose and throat).

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal

handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Swallowing may result in gastrointestinal irritation.

Component	CAS #	Amount
Calcium chloride	10043-52-4	28.0 - 42.0 %
Potassium chloride	7447-40-7	0.0 - 3.0 %
Sodium chloride	7647-14-5	0.0 - 2.0 %
Water	7732-18-5	53.0 - 72.0 %

4. First-aid measures

Eye Contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.

Skin Contact: Wash skin with plenty of water.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Extinguishing Media: This material does not burn. If exposed to fire from another source, use suitable extinguishing agent for that fire.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. This material does not burn. Fight fire for other material that is burning. Water should be applied in large quantities as fine spray.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Unusual Fire and Explosion Hazards: Not applicable.

Hazardous Combustion Products: Not applicable

6. Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Small and large spills: Contain spilled material

if possible. Absorb with materials such as: Sand. Collect in suitable and properly labeled containers.

Flush residue with plenty of water. See Section 13, Disposal Considerations, for additional

information.

3. Composition Information

Product Name: LIQUIDOW* Technical Grade Calcium Chloride
Solution

Issue Date: 01/02/2007 Page 3 of 8

Personal Precautions: Spilled material may cause a slipping hazard. Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: Product shipped/handled hot can cause thermal burns. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Storage

Keep container closed. Protect from atmospheric moisture. Product may become a solid at temperatures below 0°C (32°F) (concentrations above 36% calcium chloride).

8. Exposure Controls / Personal Protection

Exposure Limits

Component	List	Type	Value
Calcium chloride	Dow IHG	TWA	10 mg/m3
Sodium chloride	Dow IHG	TWA	10 mg/m3

Personal Protection

Eye/Face Protection: Use chemical goggles.

Skin Protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before reuse or dispose of properly.

Hand protection: Use gloves chemically resistant to this material.

Examples of preferred

glove barrier materials include: Polyethylene. Neoprene. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Avoid gloves made of: Polyvinyl alcohol ("PVA").

NOTICE: The selection

of a specific glove for a particular application and duration of use in a workplace should also

take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Atmospheric levels should be maintained below the exposure guideline.

When respiratory protection is required for certain operations, use an approved air-purifying respirator.

In dusty or misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Particulate filter.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

9. Physical and Chemical Properties

Product Name: LIQUIDOW* Technical Grade Calcium Chloride Solution

Issue Date: 01/02/2007 Page 4 of 8

Physical State Liquid

Color Clear

Odor Odorless

Flash Point - Closed Cup Not applicable

Flammable Limits In Air Lower: Not applicable Upper: Not applicable

Autoignition Temperature Not applicable

Vapor Pressure 9 - 15 mmHg @ 25 °C Literature

Boiling Point (760 mmHg) 110 - 122 °C (230 - 252 °F) Literature .

Vapor Density (air = 1) Literature same as water

Specific Gravity (H₂O = 1) 1.275 - 1.439 Literature

Freezing Point Varies

Melting Point Not applicable

Solubility in Water (by weight)

Literature completely miscible with water

pH 9.2 Estimated (10% dilution in water)

Kinematic Viscosity 2.6 cSt @ 25 °C Estimated

10. Stability and Reactivity

Stability/Instability

Stable.

Conditions to Avoid: None known.

Incompatible Materials: Avoid contact with: Sulfuric acid. Corrosive to some metals. Avoid contact

with metals such as: Brass. Ferrous metals. Mild steel. Flammable hydrogen may be generated

from contact with metals such as: Zinc. Sodium. Reaction of bromide impurity with oxidizing

materials may generate trace levels of impurities such as bromate.

Hazardous Polymerization

Will not occur.

Thermal Decomposition

Does not decompose.

11. Toxicological Information**Acute Toxicity****Ingestion**

For the major component(s): LD50, Rat 900 - 2,100 mg/kg

Skin Absorption

For the major component(s): LD50, Rabbit > 5,000 mg/kg

Genetic Toxicology

The data presented are for the following material: Calcium chloride or CaCl₂. In vitro genetic toxicity

studies were negative. The data presented are for the following material Potassium chloride. In vitro

genetic toxicity studies were positive. However, the relevance of this to humans is unknown.

12. Ecological Information

Product Name: LIQUIDOW* Technical Grade Calcium Chloride Solution

Issue Date: 01/02/2007 Page 5 of 8

CHEMICAL FATE

Data for Component: Calcium chloride

Movement & Partitioning

No bioconcentration is expected because of the relatively high water solubility. Partitioning from water to n-octanol is not applicable.

Persistence and Degradability

Biodegradation is not applicable.

Data for Component: Potassium chloride

Movement & Partitioning

Partitioning from water to n-octanol is not applicable.

Persistence and Degradability

Biodegradation is not applicable.

Data for Component: Sodium chloride

Movement & Partitioning

No bioconcentration is expected because of the relatively high water solubility. Potential for mobility in soil is very high (Koc between 0 and 50). Partitioning from water to n-octanol is not applicable.

Persistence and Degradability

Biodegradation is not applicable.

ECOTOXICITY

Data for Component: Calcium chloride

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, bluegill (*Lepomis macrochirus*): 8,350 - 10,650 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea *Daphnia magna*: 759 - 3,005 mg/l

Toxicity to Micro-organisms

EC50; activated sludge, respiration inhibition: > 1,000 mg/l

Data for Component: Potassium chloride

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100

mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (*Oncorhynchus mykiss*), 96 h: 4,236 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, water flea *Daphnia magna*, 24 h, immobilization: 590 mg/l

LC50, water flea *Ceriodaphnia dubia*, 96 h: 3,470 mg/l

Data for Component: Sodium chloride

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100

mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, fathead minnow (*Pimephales promelas*): 10,610 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea *Daphnia magna*: 4,571 mg/l

Toxicity to Micro-organisms

IC50, OECD 209 Test; activated sludge, respiration inhibition: > 1,000 mg/l

Product Name: LIQUIDOW* Technical Grade Calcium Chloride Solution

Issue Date: 01/02/2007 Page 6 of 8

13. Disposal Considerations

All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

DOW HAS NO CONTROL OVER

THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE

PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION:

Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options

include sending to a licensed, permitted: Reclaimer. Waste water treatment system. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

14. Transport Information

DOT Non-Bulk

NOT REGULATED

DOT Bulk

NOT REGULATED

IMDG

NOT REGULATED

ICAO/IATA

NOT REGULATED

This information is not intended to convey all specific regulatory or operational

requirements/information relating to this product. Additional transportation system information can be

obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29

CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning

and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard Yes

Delayed (Chronic) Health Hazard No

Fire Hazard No

Reactive Hazard No

Sudden Release of Pressure Hazard No

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and

Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Product Name: LIQUIDOW* Technical Grade Calcium Chloride Solution

Issue Date: 01/02/2007 Page 7 of 8

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous

Substances List and/or Pennsylvania Environmental Hazardous Substance List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous

Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product (when used in aqueous formulations with a chemical oxidizer such as ozone) contains a chemical known to the State of California to cause cancer. US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory

requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. Other Information

Recommended Uses and Restrictions

A calcium chloride product - Dust Control De-icing fluid. For industrial use. Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group.
Revision

Identification Number: 81498 / 0000 / Issue Date 01/02/2007 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document. Legend

N/A Not available

W/W Weight/Weight

OEL Occupational Exposure Limit

STEL Short Term Exposure Limit

TWA Time Weighted Average

ACGIH American Conference of Governmental Industrial Hygienists, Inc.

DOW IHG Dow Industrial Hygiene Guideline

WEEL Workplace Environmental Exposure Level

HAZ_DES Hazard Designation

Action Level A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with

Product Name: LIQUIDOW* Technical Grade Calcium Chloride Solution

Issue Date: 01/02/2007 Page 8 of 8

all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current,

please contact us for the most current version.